



NV-DTY

The Novus® Duty station (NV-DTY) is an audible alert device commonly used in staff lounge areas where staff members can be alerted to system calls. It is capable of producing multiple tones to differentiate call types.

- ▶ Reports 6 levels of calls with audible buzzer
- ▶ Mute button to allow temporary muting of calls
- ▶ High visible LED (multi-color) to provide visual alert
- ▶ Attractive Lexan membrane (Pantone 1C Warm Grey)
- ▶ Solid state circuitry
- ▶ Plug-in connection to system wiring

VERSIONS AND MODEL NUMBERS:

STATION TYPE	NOVUS®
Novus® Duty Alert Station	NV DTY

- For use with the West-Call® Novus® system
- For a duty station with audio, STF-2000/D (Novus)

Operating Voltage	28 VDC
Power Consumption	.06 Watts idle, .75 Watts maximum
Dimensions	4 ½"H x 2 ¾"W x 2"D
Mounting	4" square backbox with 1 gang plaster ring, Raco 190 with 768 one-gang adapter or equivalent. Minimum 2 1/8" depth required. Normal mounting is vertical.
Faceplate	Hospital Grade Polylac PA765NAT
Faceplate Color	PMS 427; Light Grey Opaque
Cable Requirement	CAT5 to associated Novus® Smart Dome when used with the Novus® system
Termination Requirement	Two RJ-45 connectors
Certifications	UL-1069 for US and Canada, E139082

NOTE: This information should not be used for final design. Consult West-Com for total system requirements. Specifications subject to change without notice.



View West-Com's complete West-Call® line of healthcare communications solutions at www.westcall.com

West-Com Nurse Call Systems, Inc.
2200 Cordelia Road • Fairfield, CA 94534 • 800-761-1180 • info@westcall.com