



SPS-1000/E



SPS-1000/E/AUX



DPS-1000/C/E/AUX



DPS-1000/C/L2



DPS-1000



DPS-1000/E

The West-Call® Patient Stations are located in the patients' rooms, providing patient(s) with a convenient means of originating calls to the nurses' station. When used with a paging system, calls can be routed directly to a patient's caregiver. The voice communication from the patient's room to the nurses' station is hands-free and two-way (duplex). Patient stations are capable of placing multiple types of calls including routine call, emergency call, code call, and two level locators. Remote devices can be connected to the patient station for additional call levels including the following:

- | | | |
|---------------------------|---------------------------|----------------------|
| ▶ Pillow Speakers | ▶ Emergency Call Stations | ▶ Code Blue Stations |
| ▶ Toilet Assist Stations | ▶ Room Smoke Detector | ▶ Code Pink Stations |
| ▶ Marc II Intercom | ▶ Bed Exit Alarms | ▶ IVAC Alarm |
| ▶ Bed-side Communications | ▶ Dome Light | ▶ TV Theft Alarms |
| | ▶ Staff Locations | ▶ Heart Monitors |

- ▶ Inlaid membrane switch with call and monitor indicator LED and call buttons
- ▶ Duplex speech for uninterrupted communication between patient and nurse
- ▶ Manual call origination via either a call button or corresponding cordset; automatic "cord out" call origination occurs when cordset is unplugged from its receptacle
- ▶ Single cordset receptacles conveniently located on station
- ▶ Red audio nurse monitor/privacy LED
- ▶ Solid state circuitry throughout for long life and reliability
- ▶ Quick connect/disconnect connector for simplified installation and service
- ▶ 2 3/4" Mylar cone speaker with a separate electret condenser microphone for full duplex communication
- ▶ Standard four-gang hospital grade ABS plastic faceplate (Three-gang box adapter ring is also available)
- ▶ Stations are fully compatible with all bedside "In-Rail" communications systems

VERSIONS AND MODEL NUMBERS:

STATION TYPE	SINGLE PATIENT STATIONS	DUAL PATIENT STATIONS
Standard Patient Station Includes Routine Call and Cancel	SPS-1000	DPS-1000
ADDITIONAL OPTIONS		
Standard Patient Station with Code	SPS-1000/C	DPS-1000/C
Standard Patient Station with Staff Emergency	SPS-1000/E	DPS-1000/E
Standard Patient Stations with 2 Level Locators	SPS-1000/L2	DPS-1000/L2
Standard Patient Station with an Auxiliary 1/4" Input Port	SPS-1000/AUX	DPS-1000/AUX
Standard Patient Station with Remote Pillow Speaker Capability	SPS-1000/R	DPS-1000/R
Standard Patient Station with Non-Standard Signaling Features	SPS-1000/F	DPS-1000/F
Standard Patient Station with Code and Staff Emergency	SPS-1000/C/E	DPS-1000/C/E
Standard Patient Station with Staff Emergency and an Auxiliary 1/4" Input Port	SPS-1000/E/AUX	DPS-1000/E/AUX

- For use with the West-Call® Odyssey Plus system
- To combine features, specify corresponding code letters (i.e. SPS-1000/C/E/F)
- Custom color faceplate option available upon request
- Station can mount over a three-gang flush wall box. Specify ADP-3/4 for mounting ring. Station will semi-flush mount to wall and extend approximately 1.1" away from the wall

Operating Voltage	27.5VDC +/-10%
Power Consumption	4 watts
Size	4 1/2"H x 8 1/4"W x 3 1/2"D
Mounting	Four-gang backbox Raco #698 (box must be level). Normal mounting is Horizontal BOX MUST BE LEVEL
Faceplate	Hospital grade ABS UL94V-0 molded thermoplastic with inlaid membrane
Faceplate Color	Standard Warm Grey (Pantone 1C). Special colors supplied on individual basis
Membrane	.010 Lexan with hardcoat finish
Membrane Color	Background color, Pantone 4C Warm Grey, copy color Grey (Pantone 1C and 11C)
Termination	Plug-on connectors allowing rapid mass termination mating connectors - Panduit needed are three (3) CE156F22-15 and one (1) CE156F22-5
Microphone	Cardiod Electret, sensitivity is -64db @ 1 microbar @ 1KHz
Speaker	2 3/4" Mylar cone with .5 ounce magnet. Minimum sensitivity is 90db SPL @ .25 watts @ 1ft.
Cable Requirements	West-Com WW-1 pair #20AWG (Power); Shielded 8 Conductor #22AWG (Data); 2 shielded pairs #22AWG (Audio), 1 conductor #22AWG home to central terminal for I.D. wire, and 2 spare wires
Certifications	UL-1069 for US and Canada. E139082



View West-Com's complete West-Call® line of healthcare communications solutions at www.westcall.com

West-Com Nurse Call Systems, Inc.
2200 Cordelia Road • Fairfield, CA 94534 • 800-761-1180 • info@westcall.com